EXECUTIVE ORDER U-R-015-0341

New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY DISPLACEMENT (liters)		FUEL TYPE	USEFUL LIFE (hours)				
2017	HFPXL03.4FSD	3.4	Diesel 8000					
	FEATURES & EMISSION C		TYPICAL EQUIPMENT APPLICATION					
Cooler Recircu	c Direct Injection, Turboo , Electronic Control Modu lation, Diesel Oxidation C Reduction - Urea, and A	ıle, Exhaust Ğas Catalyst, Selective	Loader, Tractor, Generator Set, and Other Industrial Equipment					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD			EX	(HAUST (g/kw-h	OPACITY (%)				
POWER CLASS	CATEGORY		NMHC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
56 ≤ kW < 130	Tier 4 Final	STD	0.19	0.40	N/A	5.0	0.02	N/A	N/A	N/A
		CERT	0.004	0.33		0.05	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression-Ignition Engines, Parts I-D" adopted October 20, 2005 and last amended October 25, 2012.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of December 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

U-12-015-0341
Allachmot pg 1/2 11/22/246

## Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate; mm/stroke @ peak HP (for diesel only)	5,Fuel Rate: (lbs/hr) @ peak HF (for diesels only)	P 6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peal torque		9.Emission Control Device Per SAE J1930
HFPXL03,4FSD	F5BFL414J*B	F5BFL414J*B	121 @ 2200	92	N/A	363 @ 1400	111	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414J*B	F5GFL414J*B	121 @ 2200	92	N/A	363 @ 1400	111	N/A	DDI EOM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5BFL414J*B	854F-E34TAN 4260/2200	121 @ 2200	92	N/A	363 @ 1400	111	N/A	DDI ECM TC CAC DOC SCR-U AMOX EGR.
HFPXL03,4FSD	F5BFL414J*B	Ç3.4B 4260/2200	121 @ 2200	92	N/A	363 @ 1400	111	N/A	DDI ECM TC CAC DOC SCR-U AMOX EGR,
HFPXL03,4FSD	F5BFL414H*B	F5BFL414H*B	84 @ 2200	63	N/A	262 @ 1400	78	N/A	DDI ECM TO CAC DOC SCR-U AMOX EGR.
HFPXL03,4FSD	F5GFL414H*B	F5GFL414H*B	84 @ 2200	63	N/A	262 @ 1400	78	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	. F5BFL414H*B	864F-E34TAN 4270/2200	84 @ 2200	63	. N/A	262 @ 1400	78	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5BFL414H*B	C3.4B 4270/2200	84 @ 2200	63	N/A	262 @ 1400	. 78	, N/A	DDI ECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5BFL414E*B	F5BFL414E*B	94 @ 2200	70	N/A	293 @ 1400	. 86	N/A	DDI ECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414E*B	F5GFL414E*B	94 @ 2200	70	N/A	293 @ 1400	86	N/A	DDI EOM TO CAC DOO SCR-u AMOX EGR.
HFPXL03.4FSD	F5BFL414E*B	854F-E34TAN 4276/2200	94 @ 2200	70	N/A	293 @ 1400	86	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03,4FSD	F5BFL414E*B	Ç3.4B 4276/2200	94 @ 2200	70	N/A	293 @ 1400	86	N/A	DDJ ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5BFL414A*B	F5BFL414A*B	101 @ 2200	75	N/A	: 319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR.
HFPXL03,4FSD	F5GFL414A*B	· F5GFL414A*B	101 @ 2200	75	N/A	319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-u AMOXEGR.
HFPXL03.4FSD	F6BFL414A*B	854F-E34TAN 4266/2200	101 @ 2200	75	N/A	319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR,
HFPXL03.4FSD	F5BFL414A*B	C3,4B 4266/2200	101 @ 2200	75	N/A	319 @ 1400	. : 95	N/A	DDIECM TO OAC DOC SCR-u AMOX EGR,
HFPXL03.4FSD	F5BFL414B*B	F5BFL414B*B	111 @ 2200	83	N/A	341 @ 1400 -	101	N/A	DDI ECM TO CAO DOC SCR-u AMOX EGR.
HFPXL03,4FSD	F5GFL414B*B	F5GFL414B*B	111 @ 2200	83	N/A	341 @ 1400	101	N/A	DDI ECM TO CAC DOC SCR-u AMOX EGR,
HFPXL03.4FSD	F5BFL414B*B	854F-E34TAN 4264/2200	111 @ 2200	83	N/A	341 @ 1400	. 101	N/A	DDIEGM TO CAC DOC SCR-u AMOX EGR;
HFPXL03.4FSD	F5BFL414B*B	C3.4B 4264/2200	111 @ 2200	83	N/A	341 @ 1400	101	N/A	DDI EOM TC GAC DOC SCR-u AMOX EGR.
HFPXL03,4FSD	F5BFL414F*B	F5BFL414F*B	88 @ 2500	62	N/A	274 @ 1400	84	N/A	DDI EGM TC CAC DOC SCR-u AMOX EGR,
HFPXL03.4FSD	F5GFL414F*B	F5GFL414F*B	88 @ 2500	62	. N/A	274 @ 1400	84	N/A	DDIECM TC CAC DOC SCR-u AMOX EGR,
HFPXL03,4FSD	F5BFL414F*B	854F-E34TAN 4282/2500	88 @ 2500	62	N/A	274 @ 1400	84	N/A	DDIECM TC CAC DOC SCR-u AMOXEGR,
HFPXL03.4FSD	F5BFL414F*B	C3.4B 4282/2500	88 @ 2500	62	N/A	274 @ 1400	84	N/A	DDIEGM TC CAC DOC SCR-u AMOX EGR,
HFPXL03.4FSD	F5BFL414D*B	F5BFL414D*B	101 @ 2500	70	N/A	319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414D*B	F5GFL414D*B	101 @ 2500	70	N/A	319 @ 1400	. 95	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.

M-12-015-0341
Allauhumt pg 2/2
11/22/2016

## **Engine Model Summary Template**

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6,Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9,Emission Control Device Per SAE J1930
HFPXL03.4FSD	F5BFL414D*B	854F-E34TAN 4274/2500	101 @ 2500	70	N/A	319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-U AMOXEGR.
HFPXL03.4FSD	F5BFL414D*B	C3,4B 4274/2500	101 @ 2500	70	N/A	319 @ 1400	95	N/A	DDI ECM TO CAC DOC SCR-u: AMOX EGR.
HFPXL03.4FSD	F5BFL414C*B	F5BFL414C*B	115 @ 2500	80	N/A	352 @ 1400	101	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414C*B	F5GFL414C*B	115 @ 2500	80	N/A	352 @ 1400	101	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR,
HFPXL03.4FSD	F5BFL414C*B	854F-E34TAN 4262/2500	115 @ 2500	80	N/A	352 @ 1400	101	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5BFL414C*B	C3.4B 4262/2500	115 @ 2500	80	N/A	352 @ 1400	101	N/A .	DDIECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414J*B	854F-E34TAN 4260/2200	121 @ 2200	92	N/A	363 @ 1400	111	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR.
HFPXL03.4FSD	F5GFL414J*B	C3.4B 4260/2200	121 @ 2200	92	N/A	363 @ 1400	111	N/A	DDJ ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03,4FSD	F5GFL414H*B	854F-E34TAN 4270/2200	84 @ 2200	63	N/A	262 @ 1400	78	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR.
HFPXL03.4FSD	F5GFL414H*B	C3.4B 4270/2200	84 @ 2200	63	N/A	262 @ 1400	78	N/A	DDIECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414E*B	854F-E34TAN 4276/2200	94 @ 2200	70	N/A	293 @ 1400	86	N/A	DDIECM TO CAC DOC SOR-U AMOX EGR.
HFPXL03.4FSD	F5GFL414E*B	C3.4B 4276/2200	94 @ 2200	70	N/A	293 @ 1400	86	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR,
HFPXL03.4FSD	F5GFL414A*B	854F-E34TAN 4266/2200	101 @ 2200	75	N/A	319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR.
HFPXL03.4FSD	F5GFL414A*B	C3,4B 4266/2200	101 @ 2200	75	N/A	319 @ 1400	95	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414B*B	854F-E34TAN 4264/2200	111 @ 2200	83	· N/A	341 @ 1400	101	N/A	DDIECM TO CAC DOC SCR-II AMOX EGR.
HFPXL03.4FSD	F5GFL414B*B	C3.4B 4264/2200	111 @ 2200	83	N/A	341 @ 1400	101	N/A	DDIECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414F*B	854F-E34TAN 4282/2500	88 @ 2500	62	N/A	274 @ 1400	84	N/A	DDI ECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414F*B	C3.4B 4282/2500	88 @ 2500	62	N/A_	274 @ 1400	`84	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414D*B	854F-E34TAN 4274/2500	101 @ 2500	70	N/A	319 @ 1400	95	N/A	DDIECM TO CAC DOC SCR-U AMOX EGR.
HFPXL03.4FSD	F5GFL414D*B	C3.4B 4274/2500	101 @ 2500	70	N/A	319 @ 1400	95	N/A	DDI ECM TC CAC DOC SCR-u AMOX EGR,
HFPXL03,4FSD	F5GFL414C*B	854F-E34TAN 4262/2500	115 @ 2500	80	N/A	352 @ 1400	101	N/A	DDIECM TO CAC DOC SCR-u AMOX EGR.
HFPXL03.4FSD	F5GFL414C*B	C3.4B 4262/2500	115 @ 2500	80	N/A	352 @ 1400	101	N/A	DDIECM TO CAC DOC SCR-u AMOX EGR.